

PORTABLE PERSONAL COMPUTER SYSTEM

FIELD OF THE INVENTION

The present invention relates to a personal computer system having capabilities such as computing, printing, scanning, copying, laptop docking, audio/video, etc. More particularly, the present invention relates to a compact, self-contained portable personal computer system configured and arranged in a single unit capable of computing, printing, scanning, copying, laptop docking, audio/video, etc.

BACKGROUND

Traditionally, computer users must choose between alternative computing systems for their computing needs. The user's choice of systems largely depends on the desired application. Workstations associated with a centralized server system, main frame or super computer still exists. The home or student user often purchases a traditional desktop personal computer to be kept in a den, home office, computer room or dorm room. The traditional desktop computer system contains multiple primary components such as a central processing unit, memory (e.g. Random-Access Memory, Read-Only Memory, Cache), a motherboard, a hard drive, an operating system, and sound and graphics cards. Other user-interface devices, such as the monitor, mouse and keyboard, allow a user to interact with the primary devices and are connected by separate wires of varying lengths and sizes through conventional interfaces to these primary devices. In addition to these components, a desktop computer is often connected to or networked with various peripheral devices such as a video cam, a voice system, a document scanner and printer, each of which are also hard wired by separate wires of varying lengths and sizes through conventional interfaces to the primary devices. This combination of components is highly functional and allows the user a wide range of capabilities.

The traditional desktop computer possesses numerous advantages, including but not limited to, its ability to process vast amounts of data without error, to enable its user to produce documents efficiently, and to allow the user maximum editorial control over the production of those documents. The desktop computer can automate certain ordinary tasks from turning on outside lights in the evening to brewing coffee in the morning. As a multimedia tool, the desktop computer also gives its user the ability to produce information in a graphical audio and video format, allowing studio-like presentations. Certain disadvantages, however, are inherent in the desktop computer's configuration.

Due to its bulk and weight, a desktop computer system and its multiple peripheral devices are difficult to transport. Consequently, moving the system is often only feasible when permanently relocating the system to another area and it must be disassembled and reassembled to accomplish the move. Each of the multiple peripheral and user-interface components also requires its own power supply, increasing the number of power cords, external AC adaptors, and multi-pronged electrical plugs needed for operation. The multiple peripheral components and power supplies also require a large amount of desk space for operation, and increase the complexity of and the time required for the desktop's set-up and configuration procedure. These limitations lessen the feasibility of utilizing such a system in small businesses, college dormitories, and homes.

The present invention also utilizes and improves upon certain features of the laptop computer system. Unlike the typical home or dorm room user, a business traveler often purchases a laptop computer. A laptop computer is a portable personal computer that avoids many of the desktop computer's disadvantages. Because of its size, a laptop computer is easy to transport. Its internal configuration of components such as the keyboard, cursor control sensor, and monitor allows for minimal set-up and configuration time and requires less desk space for operation. At typically less than 10 lbs., a laptop

computer also weighs less than a desktop computer. However, a laptop computer lacks the functionality and comfort of a traditional desktop computer.

A laptop computer's screen usually presents substantially less viewing area than a desktop computer's monitor. Similarly, a laptop computer's keyboard is usually smaller than a standard keyboard, and a laptop computer's trackball or touch pad may be more difficult to use than a standard mouse. A laptop computer generally has less storage space on its internal disk drive than a traditional desktop. Also, a laptop computer often allows its user to access only one type of disk drive at a time. To compensate for this lack of functionality and comfort, a laptop computer can support added peripheral devices such as a full sized keyboard and mouse, one or more speakers, and a variety of external storage devices, all hard wired to interfaces and/or to each other. The addition of these devices however creates transportation and weight limitations similar to those of a desktop computer.

Accordingly, improvements on the existing personal computers are desired. For example, it would be advantageous to provide a combination of primary computer devices and peripheral computer devices within a single system enclosure, wherein the enclosure is easily transported and requires minimal desk space and set-up time for operation.

SUMMARY

To resolve the above and other problems and disadvantages of the existing personal computer systems, the present invention provides a combination of the functionality and capability of a desktop computer and its various peripheral devices, including a document scanner and printer, with the convenience and portability of a laptop computer thereby reducing the system's weight and the desk space required for operation, and simplifying the system's set-up procedures.

In one embodiment of the present invention, multiple primary and peripheral devices, including a central processing unit, at least one memory device, a motherboard, a hard drive, sound and graphics cards, a video cam, a microphone, one or more speakers, a document scanning device and a printing unit, etc., are configured and arranged in a single system enclosure equipped with a handle and at least one transport wheel.

A traditional system equipped with various external devices often requires a complicated set-up procedure. Typically, a traditional system will come packaged with various instructions and hints for performing the often time-consuming procedure. One advantage of the present invention is that it allows a consumer to purchase a pre-configured system, requiring no time-consuming and complicated set-up procedures. In one embodiment of the present invention, an operating system may be pre-installed, and the requisite software and drivers required for operating the included devices may be embedded as well. Also, the present invention minimizes the number of documents normally included in the purchase of a personal computer that describe the system's set-up procedures and operation.

Typically, the need to connect various peripheral and user-interface devices to a personal computer clutters the desk and floor space around such a system. A printer, a scanner, one or more speakers, a video cam, and a monitor, all connected to a standard personal computer, would each need a cable connecting the particular device to the personal computer and a power cord connecting the particular device to a power source. In most instances, this configuration leads to a tangle of wires connected to a power strip, causing an unsightly and unsafe working area that impedes a user's ability to quickly identify the location of a particular device's interface with the computer and may result in damage to the connecting cords and cables. One advantage of the present invention is that it eliminates these concerns by combining the separate power supplies for each of the

various devices into a single power supply serving all functions of the present invention. In one embodiment of the present invention, a single electrical prong disposed outside of a system enclosure and a single power cord connected to the electrical prong are the only pieces of the system's power supply visible to a user. A user can power the entire system by simply plugging the power cord into a power outlet and turning the power on the system enclosure.

Another advantage of the present invention is that it eliminates the bulky monitor traditionally associated with a desktop computer system and includes a flat screen display that is connected to the system's power supply. In one embodiment of the present invention, a flat screen display is hinged to a system enclosure so that in a closed position the flat screen display folds into the system enclosure, and in an open position the flat screen display remains upright at a height sufficient to minimize the strain on a user's neck.

In further minimizing the number of external devices and corresponding connection cords or cables, one embodiment of the present invention includes an infrared mouse and an infrared keyboard. An infrared sensor within the computer system provides an optical interface between the system and the mouse and between the system and the keyboard. The infrared keyboard can be stored completely within the system enclosure in a keyboard storage tray. By storing the infrared keyboard within the keyboard storage tray when not in use, the user can completely remove the infrared keyboard from view thereby further reducing the clutter surrounding the system and maintaining an aesthetically pleasing work area. Further in one embodiment, a docking station is built in the keyboard storage tray for docking with another computer system.

Because of its various components contained in a single system enclosure, the present invention provides an easy-to-use, multi-functional system within a portable

housing. Further, the overall weight of the system is considerably reduced. These features and other aspects and advantages of the present invention will become clear after examining the following description, appended claims, and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the present invention are set forth in the appended claims. The invention itself will be best understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, wherein:

Figure 1 is a front perspective view of one embodiment of a portable personal computer system, in accordance with the principles of the present invention, having a flat screen display raised to an open position, a video cam integral to the flat screen display, and a front panel opened to illustrate an infrared keyboard and an infrared mouse stored in a tray, and a docking station built in the tray.

Figure 2 is a bottom perspective view of one embodiment of a portable personal computer system, in accordance with the principles of the present invention, showing an extended handle capable of pulling the computer system and a top handle for carrying/lifting the computer system.

Figure 3 is a rear perspective view of one embodiment of a portable personal computer system, in accordance with the principles of the present invention, showing a side panel in an open position to illustrate media ports, and showing cooling facilities and interconnects on the back of the computer system.

Figure 4 is a perspective view of one embodiment of a portable personal computer, in accordance with the principles of the present invention, being transported by a pulling handle extended out of a system enclosure.

Figure 5 is a perspective view of one embodiment of a portable personal computer system, in accordance with the principles of the present invention, housed in a carrying case with a pulling handle extended out of the carrying case.

Figure 6 is a perspective view of one embodiment of a portable personal computer system, in accordance with the principles of the present invention, showing bottom of the carrying case with wheels for transport and stops for stand.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention relates to a personal computer system having capabilities such as computing, printing, scanning, copying, laptop docking, audio/video, etc. More particularly, the present invention relates to a compact, self-contained portable personal computer system configured and arranged in a single unit capable of computing, printing, scanning, copying, laptop docking, audio/video, etc.

The present invention allows business travelers, students, and/or home users to utilize various components of a traditional desktop computer system without being limited by the time required to set-up and/or configure a desktop system, the space needed to operate a desktop system, and the inability to transport a desktop system. Any reference in this detailed description to front and back, right and left, top and bottom and upper and lower is intended for convenience of description, not to limit the present invention or its components to any one position or special orientation.

Referring now to the drawings and particularly to **FIGS. 1 and 2**, one embodiment of a portable personal computer system **20**, in accordance with the principles of the present invention, is illustrated. The portable personal computer system **20** includes a system enclosure **22** preferably made of metal and/or plastic and formed in a rectangular

shape having a top, a bottom, and four sides. The system enclosure 22 accommodates the features of the present invention and maintains a flat screen display 24 at a sufficient height to minimize strain on a user's neck while operating the portable personal computer system 20.

The system enclosure 22 includes a front cover 26 rotatably hinged at one end of the system enclosure 22. The front cover 26 may include a standard fastening mechanism (not shown) so that in its closed position, the front cover 26 remains closed until the fastening mechanism is released. A carrying handle 28 is disposed on the outside of the front cover 26 and capable of supporting the full weight of the portable personal computer system 20. The carrying handle 28 allows the user to carry the portable personal computer system 20 when the front cover 26 is in the closed position, and lift the system 20 into a carrying case (FIGS. 5 and 6) for transportation.

The system enclosure 22 preferably provides a rigid structural frame for housing the system's central processing unit (CPU) that contains multiple memory circuits, such as ROM and RAM, etc. The system enclosure 22 is connected to a power supply (not shown) via a power supply port 30 (FIG. 3). The system enclosure 22 further includes air vents 32 and may also include at least one fan 33 (FIG. 3) so as to allow air to circulate over the computer components inside the system enclosure 22 to sufficiently cool the personal computer system 20.

As shown in FIG. 1, the front cover 26 is in its open position. A tray 34 is disposed at the bottom of the system enclosure 22 behind the front cover 26 and is pulled out of the system enclosure 22. An infrared mouse 35 and an infrared keyboard 36 are stored in the tray 34 when they are not in use. In FIG. 1, the infrared mouse 35 and the infrared keyboard 36 are removed from the tray 34 for illustration purposes. An infrared

sensor (not shown) for optical communication with the infrared mouse **35** and the infrared keyboard **36** is electrically connected to the computer components, such as the CPU, and mounted therein and proximate the front side of the portable personal computer system **20**. The infrared mouse **35** and the infrared keyboard **36** transmit data to the infrared sensor in the manner known in the art. It is appreciated that the infrared sensor can be installed on a display **38** so that the infrared mouse **35** can be used like a laser pointer known in the art to minimize wrist movement by a user for operating the system, thereby reducing susceptibility to carpal tunnel syndrome. Further, the infrared keyboard **36**, such as an infrared alpha-numeric keyboard, allows a user to efficiently interface with the portable personal computer system **20** without fixed connections. Input from a user is optically transmitted from the infrared keyboard **36** and/or mouse **35** to the infrared sensor, and is transformed to electronic signals to control a variety of computer processes.

In addition that the tray **26** is capable of fully housing the infrared keyboard **36**, the tray **26** can slide outside of the system enclosure **22** when the front cover **26** is in an open position. The tray **26** may also contain a docking port **40** that allows the transfer of data between another computer, such as a laptop computer, and the portable personal computer system **20**, and allows the portable personal computer system **20** to serve as a base computer if another computer is required for remote operations.

Also in **FIG. 1**, connected to the CPU through standard interfaces are the system's data storage devices, including a hard drive (not shown), a floppy disc and/or zip drive **42**, and a CD and/or DVD drive **44**. The hard drive is mounted inside the system enclosure **22** and at the base of the portable personal computer **20** in a compact manner. The floppy disc and/or zip drive **42** and the CD and/or DVD drive **44** are mounted in one or more standard storage bays within the system enclosure **22** in a manner that allows a

user to place appropriate storage medium within the drives through a slot of the system enclosure **22** of the portable personal computer system **20**.

A document scanning unit or module is also connected to the CPU and to the power supply through a standard electrical connection. The document scanning module captures images and text and allows the user to save the information to the memory components of the portable personal computer system **20**. The document scanning module includes a scanning cover **46** that aids the scanning software in determining the size of the object being scanned, a transparent area **48** upon which a user places the document to be scanned, a scan head having components, such as mirrors, lenses, filters, and CCD array, etc., for producing an image of a document to be scanned, a stepper motor and belt combination providing mechanical means by which the scan head traverses the document to be scanned, a stabilizer bar insuring that the scan head traverses smoothly under the document to be scanned, and a lamp to illuminate the document to be scanned.

The scanning cover **46** is hinged to the system enclosure **22** via a standard hinge **50** so that in an open position, the scanning cover **46** can be positioned in a variety of angles including approximately perpendicular to the transparent area **48**, and in a closed position, the scanning cover **46** can rest immediately over the transparent area **48**. The standard hinge **50** is attached to the system enclosure **22** and, in the preferred embodiment, the hinge **50** is located along one side of the transparent area **48**. The transparent area **48** is located in the upper portion of the system enclosure **22** and is visible when the scanning cover **46** is in its open position, allowing a user to place the document to be scanned directly on the transparent area **48** and below the closed scanning

cover **46** with the particular side of the document to be scanned facing the transparent area **48**.

The lamp is located within the system enclosure **22** in a position that enables to illuminate the entire document to be scanned. The scan head is positioned beneath the transparent area **48** and mounted for longitudinal movement across the document to be scanned. The stabilizer bar may be mounted within the system enclosure **22** by mounting brackets positioned near the right and left sides of the system enclosure **22** and in the same direction as the longitudinal movement of the scan head. A stepper motor (not shown) connected to the power supply through an electrical interface may be located within the system enclosure **22** and mounted for minimizing interference with the other components of the portable personal computer system **20**. Upon input from a user directing the scanning operation to begin, the stepper motor drives the belt system that pulls the scan head along the upper side of the stabilizer bar and below the document to be scanned. The scan head may be allowed to move within a limited range of travel by the stepper motor, as determined by the size of the document to be scanned. The portable personal computer system **20** may be installed with the scanning software necessary to transform the images retrieved by the scan head into full color electronic pictures for eventual manipulation and transmission by the user.

A printing unit or module may be included within the system enclosure **22** and is electrically connected to the CPU and to the power supply. The printing unit allows the user to print the images and text captured by the scanning device or to print documents or faxes contained in the computer memory. The printing unit may utilize the stepper motor and belt system mounted within the system enclosure **22**, may be synchronized therewith, or all units may be synchronized with a computer clock. A document feed-in slot **52**

(FIG. 3) and a document exit slot **54** are preferably located horizontally along the sides of and towards the top of the system enclosure **22**. A roller assembly, mounted within the system enclosure **22** and driven by the stepper motor and belt system, creates a document feed path directing a sheet of paper from the document feed-in slot **52** to the document exit slot **54**. The printing module is mounted near the document feed-in slot **52** and aimed directly at the document feed path in such a way that a printing operation and a scanning operation share similar components but operate independently of one another. The printing module may be any compact commercially available printing module, such as an inkjet, dot-matrix, laser, etc.

Upon input from a user directing a printing operation to begin, the stepper motor drives the belt system that rotates the roller assembly and pulls a sheet of paper from the document feed-in slot **52** and along the document feed path. The printing unit prints the desired pattern, and the roller assembly carries the sheet of paper towards the document exit slot **54** and out of the system enclosure **22**. Storage trays may be provided at the document feed-in slot **52** or at the document exit slot **54** to receive the printed documents. Printing software and drivers are pre-installed in the portable personal computer system **20** to allow immediate operation of the printing unit.

The display **38** is preferably a flat screen display. The flat screen display **38** is located within a display frame **56** and hinged to the system enclosure **22** via the standard hinge **50**, so that in an open position, the flat screen display **38** can be positioned in a variety of angles including approximately perpendicular to the top of the system enclosure **22**, and in a closed position, the flat screen display **38** can be positioned immediately over the closed scanner cover **46**. The hinge **50** is configured and arranged to connect both the flat screen display **38** and the scanner cover **46**, and allows each to

rotate independently of one another. The flat screen display **38**, a standard liquid crystal display of the type well known in the art or of any new technology in the future, visually displays the output generated by the software applications, such as a video card, and is connected electrically to the system's internal circuitry and to the system's power supply. The connection can be provided between a slot within the display frame **56** side of the hinge **50** and a corresponding slot within the system enclosure **22** side of the hinge **50**. A cable connecting the flat screen display **38** to the internal circuitry can pass through the slots (not shown) to the system's internal circuitry regardless of the display frame's **56** positioning. In the preferred embodiment, the display frame **56** contains a standard fastening mechanism (not shown) that locks the flat screen display **38** and the scanning cover **46** in place while not in use. When needed, the user can unlock the fastening mechanism and rotate the flat screen display **38** and the scanning cover **46** in any desired position.

As part of a complete PC telephony system, one embodiment of the present invention includes a video cam **58**, housed within a camera mounting bracket **60**, for recording the surrounding view. A camera mounting bracket **60** is preferably located in the upper portion of and within the edge of the display frame **56**. The mounting bracket **60** may include an opening suitably sized so that the video cam **58** can be force-fit into and housed within the opening. The video cam **58** may be of any number of standard mini video cams commercially available. The video cam **58** is electrically connected to the power supply and to the appropriate internal components of the portable personal computer system **20** by a cable that is mounted within the display frame **56** and, along with the flat screen display's **38** electrical connections, passes through the slots in the hinge **50** described previously. The video cam **58** may be slightly recessed from the surface of the display frame **56** to avoid contact between the video cam **58** and the system

enclosure **22** when the display frame **56** is in the closed position. In the preferred embodiment, the video cam **58** and the camera mounting bracket **60** are arranged or positioned in such a way that avoids interference with the locking mechanism on the display frame **56**.

Along with the video cam **58**, the portable personal computer system's **20** complete PC telephony system may include a modem, at least one speaker, a microphone, a sound card, a video card, and PC telephony software, each fully enclosed within the system enclosure **22**. The modem, sound card, and video card are mounted within and at the base of the portable personal computer system **20** in a compact manner similar to that of a portable laptop computer. The microphone and speaker(s) are mounted within and along a side of the system enclosure **22**.

Slots **62** are located along the outside of the system enclosure **22** so that the sound-emitting side of the speaker and the sound-receiving side of the microphone are located directly behind the slots **62** to allow a user to clearly hear sound from the speaker(s) and to allow the telephony system to clearly receive and record sound from the user. These components are connected to the power supply and/or the motherboard through conventional interfaces. The PC telephony system allows communications with remote terminals and supports voice communication, voice messaging, faxes, video conferencing, and call, voice and e-mail routing.

Referring to **FIG. 3**, the power supply is connected to the CPU through standard interfaces and contained within a separate compartment located within and at the back side of the system enclosure **22** with standard mounting brackets. The power supply is designed in such a way that the power supply is contained within the system enclosure **22**, and the electrical plug **30** located at the back of the system enclosure **22** can be the only

visibly exposed component of the computer system **20**. The electrical plug **30** is attached via a standard interface to an AC bus. The AC bus supplies power to each AC component of the portable personal computer system **20** through conventional interfaces. The AC bus also supplies power to a transformer which may reduce the AC voltage to an appropriate amount and convert the AC voltage to DC voltage. DC power is then supplied to each of the DC components in the portable personal computer system **20**. The system's use of a simple power cord attached to a power source and to the plug **30** on the back side of the system enclosure **22** minimizes the clutter, confusion, and safety hazards of multiple power sources typically associated with a traditional computer system.

Also in **FIG. 3**, a series of ports **64** are disposed on the side of the system enclosure **22** allowing the portable personal computer system **20** to connect to a variety of external devices, including digital cameras, network cards, modems and information storage devices. The ports **64** are electrically connected directly to the system's motherboard. A port cover **66** is rotatably hinged at one end to the system enclosure **22** and contains a standard fastening mechanism so that in a closed position, the port cover **66** remains closed until the fastening mechanism is released. The port cover **66** protects the ports **64** in its closed position and allows full user access to the ports **64** in its open position. The backside of the system enclosure **22** also contains various I/O ports **68** for connecting the portable personal computer system **20** to devices, such as an external printer, monitor and keyboard. The I/O ports **68** can be connected directly to the system's motherboard.

Referring to **FIG. 4**, the portable personal computer system **20** may include an extendable carrying handle **70**, which maximizes a user's ability to transport the system **20**. During operation of the portable personal computer system **20**, the extendable

carrying handle **70** can be fully contained within a handle storage compartment **72** (FIG. 2) in the bottom side of the system enclosure **22**. The end of the extendable carrying handle **70** can be positioned flush with the front cover **26**. When transporting the personal portable computer system **20**, the extendable carrying handle **70** can be extended for ease in transportation. The extendable carrying handle **70** can extend a distance slightly less than the length of the portable personal computer system **20**, and is held at that distance by a stopping mechanism that prevents the extendable carrying handle **70** from sliding out of the handle storage compartment **72**.

Referring to FIGS. 5 and 6, the portable personal computer system **20** may include a case **74**, such as a static free travel case, capable of housing, in its entirety, the portable personal computer system **20**. The case **74** may be customized to fit the unique design of the portable personal computer system **20**, and to allow the full extension of the extendable carrying handle **70**. In the preferred embodiment, the case **74** includes an opening **76** positioned immediately over the extended carrying handle **70** so that a user can carry the portable personal computer system **20** by the extendable handle **70** when the system is completely enclosed by the case **70**. On its bottom side, the case **70** may include one or more wheels **78** and one or more stops **80**, allowing a user to comfortably carry the portable personal computer system **20** like a portable suitcase by dragging the system across and slightly above the ground. The wheels **78** and stops **80** are arranged in a particular design to maintain the portable personal computer system **20** in a stable vertical or upright standing position when not in use.

It will be appreciated that other computer modules or units can be included in the system **20**. For example, a copying module or unit may be included in the system. It will also be appreciated that the modules or units described above may be configured in

separate modules or units and arranged in a single enclosure according to their general functionalities in a system.

The described portable personal computer system **20** allows a user to efficiently access a variety of computer components while minimizing the desk space and set-up time needed for operation, and maximizing the user's ability to transport the system. The present invention is described in terms of an exemplary embodiment. However, one of ordinary skill in the art would recognize that the principles involved in the present invention can be easily implemented in various configuration designs, and that any such variation would be within the scope of the present invention.

FIG. 1
FIG. 2
FIG. 3
FIG. 4
FIG. 5
FIG. 6
FIG. 7
FIG. 8
FIG. 9
FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100
FIG. 101
FIG. 102
FIG. 103
FIG. 104
FIG. 105
FIG. 106
FIG. 107
FIG. 108
FIG. 109
FIG. 110
FIG. 111
FIG. 112
FIG. 113
FIG. 114
FIG. 115
FIG. 116
FIG. 117
FIG. 118
FIG. 119
FIG. 120
FIG. 121
FIG. 122
FIG. 123
FIG. 124
FIG. 125
FIG. 126
FIG. 127
FIG. 128
FIG. 129
FIG. 130
FIG. 131
FIG. 132
FIG. 133
FIG. 134
FIG. 135
FIG. 136
FIG. 137
FIG. 138
FIG. 139
FIG. 140
FIG. 141
FIG. 142
FIG. 143
FIG. 144
FIG. 145
FIG. 146
FIG. 147
FIG. 148
FIG. 149
FIG. 150
FIG. 151
FIG. 152
FIG. 153
FIG. 154
FIG. 155
FIG. 156
FIG. 157
FIG. 158
FIG. 159
FIG. 160
FIG. 161
FIG. 162
FIG. 163
FIG. 164
FIG. 165
FIG. 166
FIG. 167
FIG. 168
FIG. 169
FIG. 170
FIG. 171
FIG. 172
FIG. 173
FIG. 174
FIG. 175
FIG. 176
FIG. 177
FIG. 178
FIG. 179
FIG. 180
FIG. 181
FIG. 182
FIG. 183
FIG. 184
FIG. 185
FIG. 186
FIG. 187
FIG. 188
FIG. 189
FIG. 190
FIG. 191
FIG. 192
FIG. 193
FIG. 194
FIG. 195
FIG. 196
FIG. 197
FIG. 198
FIG. 199
FIG. 200
FIG. 201
FIG. 202
FIG. 203
FIG. 204
FIG. 205
FIG. 206
FIG. 207
FIG. 208
FIG. 209
FIG. 210
FIG. 211
FIG. 212
FIG. 213
FIG. 214
FIG. 215
FIG. 216
FIG. 217
FIG. 218
FIG. 219
FIG. 220
FIG. 221
FIG. 222
FIG. 223
FIG. 224
FIG. 225
FIG. 226
FIG. 227
FIG. 228
FIG. 229
FIG. 230
FIG. 231
FIG. 232
FIG. 233
FIG. 234
FIG. 235
FIG. 236
FIG. 237
FIG. 238
FIG. 239
FIG. 240
FIG. 241
FIG. 242
FIG. 243
FIG. 244
FIG. 245
FIG. 246
FIG. 247
FIG. 248
FIG. 249
FIG. 250
FIG. 251
FIG. 252
FIG. 253
FIG. 254
FIG. 255
FIG. 256
FIG. 257
FIG. 258
FIG. 259
FIG. 260
FIG. 261
FIG. 262
FIG. 263
FIG. 264
FIG. 265
FIG. 266
FIG. 267
FIG. 268
FIG. 269
FIG. 270
FIG. 271
FIG. 272
FIG. 273
FIG. 274
FIG. 275
FIG. 276
FIG. 277
FIG. 278
FIG. 279
FIG. 280
FIG. 281
FIG. 282
FIG. 283
FIG. 284
FIG. 285
FIG. 286
FIG. 287
FIG. 288
FIG. 289
FIG. 290
FIG. 291
FIG. 292
FIG. 293
FIG. 294
FIG. 295
FIG. 296
FIG. 297
FIG. 298
FIG. 299
FIG. 300
FIG. 301
FIG. 302
FIG. 303
FIG. 304
FIG. 305
FIG. 306
FIG. 307
FIG. 308
FIG. 309
FIG. 310
FIG. 311
FIG. 312
FIG. 313
FIG. 314
FIG. 315
FIG. 316
FIG. 317
FIG. 318
FIG. 319
FIG. 320
FIG. 321
FIG. 322
FIG. 323
FIG. 324
FIG. 325
FIG. 326
FIG. 327
FIG. 328
FIG. 329
FIG. 330
FIG. 331
FIG. 332
FIG. 333
FIG. 334
FIG. 335
FIG. 336
FIG. 337
FIG. 338
FIG. 339
FIG. 340
FIG. 341
FIG. 342
FIG. 343
FIG. 344
FIG. 345
FIG. 346
FIG. 347
FIG. 348
FIG. 349
FIG. 350
FIG. 351
FIG. 352
FIG. 353
FIG. 354
FIG. 355
FIG. 356
FIG. 357
FIG. 358
FIG. 359
FIG. 360
FIG. 361
FIG. 362
FIG. 363
FIG. 364
FIG. 365
FIG. 366
FIG. 367
FIG. 368
FIG. 369
FIG. 370
FIG. 371
FIG. 372
FIG. 373
FIG. 374
FIG. 375
FIG. 376
FIG. 377
FIG. 378
FIG. 379
FIG. 380
FIG. 381
FIG. 382
FIG. 383
FIG. 384
FIG. 385
FIG. 386
FIG. 387
FIG. 388
FIG. 389
FIG. 390
FIG. 391
FIG. 392
FIG. 393
FIG. 394
FIG. 395
FIG. 396
FIG. 397
FIG. 398
FIG. 399
FIG. 400
FIG. 401
FIG. 402
FIG. 403
FIG. 404
FIG. 405
FIG. 406
FIG. 407
FIG. 408
FIG. 409
FIG. 410
FIG. 411
FIG. 412
FIG. 413
FIG. 414
FIG. 415
FIG. 416
FIG. 417
FIG. 418
FIG. 419
FIG. 420
FIG. 421
FIG. 422
FIG. 423
FIG. 424
FIG. 425
FIG. 426
FIG. 427
FIG. 428
FIG. 429
FIG. 430
FIG. 431
FIG. 432
FIG. 433
FIG. 434
FIG. 435
FIG. 436
FIG. 437
FIG. 438
FIG. 439
FIG. 440
FIG. 441
FIG. 442
FIG. 443
FIG. 444
FIG. 445
FIG. 446
FIG. 447
FIG. 448
FIG. 449
FIG. 450
FIG. 451
FIG. 452
FIG. 453
FIG. 454
FIG. 455
FIG. 456
FIG. 457
FIG. 458
FIG. 459
FIG. 460
FIG. 461
FIG. 462
FIG. 463
FIG. 464
FIG. 465
FIG. 466
FIG. 467
FIG. 468
FIG. 469
FIG. 470
FIG. 471
FIG. 472
FIG. 473
FIG. 474
FIG. 475
FIG. 476
FIG. 477
FIG. 478
FIG. 479
FIG. 480
FIG. 481
FIG. 482
FIG. 483
FIG. 484
FIG. 485
FIG. 486
FIG. 487
FIG. 488
FIG. 489
FIG. 490
FIG. 491
FIG. 492
FIG. 493
FIG. 494
FIG. 495
FIG. 496
FIG. 497
FIG. 498
FIG. 499
FIG. 500
FIG. 501
FIG. 502
FIG. 503
FIG. 504
FIG. 505
FIG. 506
FIG. 507
FIG. 508
FIG. 509
FIG. 510
FIG. 511
FIG. 512
FIG. 513
FIG. 514
FIG. 515
FIG. 516
FIG. 517
FIG. 518
FIG. 519
FIG. 520
FIG. 521
FIG. 522
FIG. 523
FIG. 524
FIG. 525
FIG. 526
FIG. 527
FIG. 528
FIG. 529
FIG. 530
FIG. 531
FIG. 532
FIG. 533
FIG. 534
FIG. 535
FIG. 536
FIG. 537
FIG. 538
FIG. 539
FIG. 540
FIG. 541
FIG. 542
FIG. 543
FIG. 544
FIG. 545
FIG. 546
FIG. 547
FIG. 548
FIG. 549
FIG. 550
FIG. 551
FIG. 552
FIG. 553
FIG. 554
FIG. 555
FIG. 556
FIG. 557
FIG. 558
FIG. 559
FIG. 560
FIG. 561
FIG. 562
FIG. 563
FIG. 564
FIG. 565
FIG. 566
FIG. 567
FIG. 568
FIG. 569
FIG. 570
FIG. 571
FIG. 572
FIG. 573
FIG. 574
FIG. 575
FIG. 576
FIG. 577
FIG. 578
FIG. 579
FIG. 580
FIG. 581
FIG. 582
FIG. 583
FIG. 584
FIG. 585
FIG. 586
FIG. 587
FIG. 588
FIG. 589
FIG. 590
FIG. 591
FIG. 592
FIG. 593
FIG. 594
FIG. 595
FIG. 596
FIG. 597
FIG. 598
FIG. 599
FIG. 600
FIG. 601
FIG. 602
FIG. 603
FIG. 604
FIG. 605
FIG. 606
FIG. 607
FIG. 608
FIG. 609
FIG. 610
FIG. 611
FIG. 612
FIG. 613
FIG. 614
FIG. 615
FIG. 616
FIG. 617
FIG. 618
FIG. 619
FIG. 620
FIG. 621
FIG. 622
FIG. 623
FIG. 624
FIG. 625
FIG. 626
FIG. 627
FIG. 628
FIG. 629
FIG. 630
FIG. 631
FIG. 632
FIG. 633
FIG. 634
FIG. 635
FIG. 636
FIG. 637
FIG. 638
FIG. 639
FIG. 640
FIG. 641
FIG. 642
FIG. 643
FIG. 644
FIG. 645
FIG. 646
FIG. 647
FIG. 648
FIG. 649
FIG. 650
FIG. 651
FIG. 652
FIG. 653
FIG. 654
FIG. 655
FIG. 656
FIG. 657
FIG. 658
FIG. 659
FIG. 660
FIG. 661
FIG. 662
FIG. 663
FIG. 664
FIG. 665
FIG. 666
FIG. 667
FIG. 668
FIG. 669
FIG. 670
FIG. 671
FIG. 672
FIG. 673
FIG. 674
FIG. 675
FIG. 676
FIG. 677
FIG. 678
FIG. 679
FIG. 680
FIG. 681
FIG. 682
FIG. 683
FIG. 684
FIG. 685
FIG. 686
FIG. 687
FIG. 688
FIG. 689
FIG. 690
FIG. 691
FIG. 692
FIG. 693
FIG. 694
FIG. 695
FIG. 696
FIG. 697
FIG. 698
FIG. 699
FIG. 700
FIG. 701
FIG. 702
FIG. 703
FIG. 704
FIG. 705
FIG. 706
FIG. 707
FIG. 708
FIG. 709
FIG. 710
FIG. 711
FIG. 712
FIG. 713
FIG. 714
FIG. 715
FIG. 716
FIG. 717
FIG. 718
FIG. 719
FIG. 720
FIG. 721
FIG. 722
FIG. 723
FIG. 724
FIG. 725
FIG. 726
FIG. 727
FIG. 728
FIG. 729
FIG. 730
FIG. 731
FIG. 732
FIG. 733
FIG. 734
FIG. 735
FIG. 736
FIG. 737
FIG. 738
FIG. 739
FIG. 740
FIG. 741
FIG. 742
FIG. 743
FIG. 744
FIG. 745
FIG. 746
FIG. 747
FIG. 748
FIG. 749
FIG. 750
FIG. 751
FIG. 752
FIG. 753
FIG. 754
FIG. 755
FIG. 756
FIG. 757
FIG. 758
FIG. 759
FIG. 760
FIG. 761
FIG. 762
FIG. 763
FIG. 764
FIG. 765
FIG. 766
FIG. 767
FIG. 768
FIG. 769
FIG. 770
FIG. 771
FIG. 772
FIG. 773
FIG. 774
FIG. 775
FIG. 776
FIG. 777
FIG. 778
FIG. 779
FIG. 780
FIG. 781
FIG. 782
FIG. 783
FIG. 784
FIG. 785
FIG. 786
FIG. 787
FIG. 788
FIG. 789
FIG. 790
FIG. 791
FIG. 792
FIG. 793
FIG. 794
FIG. 795
FIG. 796
FIG. 797
FIG. 798
FIG. 799
FIG. 800
FIG. 801
FIG. 802
FIG. 803
FIG. 804
FIG. 805
FIG. 806
FIG. 807
FIG. 808
FIG. 809
FIG. 810
FIG. 811
FIG. 812
FIG. 813
FIG. 814
FIG. 815
FIG. 816
FIG. 817
FIG. 818
FIG. 819
FIG. 820
FIG. 821
FIG. 822
FIG. 823
FIG. 824
FIG. 825
FIG. 826
FIG. 827
FIG. 828
FIG. 829
FIG. 830
FIG. 831
FIG. 832
FIG. 833
FIG. 834
FIG. 835
FIG. 836
FIG. 837
FIG. 838
FIG. 839
FIG. 840
FIG. 841
FIG. 842
FIG. 843
FIG. 844
FIG. 845
FIG. 846
FIG. 847
FIG. 848
FIG. 849
FIG. 850
FIG. 851
FIG. 852
FIG. 853
FIG. 854
FIG. 855
FIG. 856
FIG. 857
FIG. 858
FIG. 859
FIG. 860
FIG. 861
FIG. 862
FIG. 863
FIG. 864
FIG. 865
FIG. 866
FIG. 867
FIG. 868
FIG. 869
FIG. 870
FIG. 871
FIG. 872
FIG. 873
FIG. 874
FIG. 875
FIG. 876
FIG. 877
FIG. 878
FIG. 879
FIG. 880
FIG. 881
FIG. 882
FIG. 883
FIG. 884
FIG. 885
FIG. 886
FIG. 887
FIG. 888
FIG. 889
FIG. 890
FIG. 891
FIG. 892
FIG. 893
FIG. 894
FIG. 895
FIG. 896
FIG. 897
FIG. 898
FIG. 899
FIG. 900
FIG. 901
FIG. 902
FIG. 903
FIG. 904
FIG. 905
FIG. 906
FIG. 907
FIG. 908
FIG. 909
FIG. 910
FIG. 911
FIG. 912
FIG. 913
FIG. 914
FIG. 915
FIG. 916
FIG. 917
FIG. 918
FIG. 919
FIG. 920
FIG. 921
FIG. 922
FIG. 923
FIG. 924
FIG. 925
FIG. 926
FIG. 927
FIG. 928
FIG. 929
FIG. 930
FIG. 931
FIG. 932
FIG. 933
FIG. 934
FIG. 935
FIG. 936
FIG. 937
FIG. 938
FIG. 939
FIG. 940
FIG. 941
FIG. 942
FIG. 943
FIG. 944
FIG. 945
FIG. 946
FIG. 947
FIG. 948
FIG. 949
FIG. 950
FIG. 951
FIG. 952
FIG. 953
FIG. 954
FIG. 955
FIG. 956
FIG. 957
FIG. 958
FIG. 959
FIG. 960
FIG. 961
FIG. 962
FIG. 963
FIG. 964
FIG. 965
FIG. 966
FIG. 967
FIG. 968
FIG. 969
FIG. 970
FIG. 971
FIG. 972
FIG. 973
FIG. 974
FIG. 975
FIG. 976
FIG. 977
FIG. 978
FIG. 979
FIG. 980
FIG. 981
FIG. 982
FIG. 983
FIG. 984
FIG. 985
FIG. 986
FIG. 987
FIG. 988
FIG. 989
FIG. 990
FIG. 991
FIG. 992
FIG. 993
FIG. 994
FIG. 995
FIG. 996
FIG. 997
FIG. 998
FIG. 999
FIG. 1000